## **SPS PRIMARY – WINTER**

## - the world's first PCB barrier that cures at 1 degree

SPS Primary Winter is a further development of the recognized high-tech diffusion barrier "SPS Primary", which is specifically designed to stop the outgassing of surfaces containing PCBs.

SPS Primary - Winter offers the same very high barrier properties, but cures at just 1 degree Celsius. SPS with Primary Winter therefore offers a significantly longer and more flexible period for waterproofing and renovation work. In the past, waterproofing work was only possible at temperatures above 10 degrees per day, and working at lower temperatures led to increased project costs, winter measures and possibly even delays.

SPS Primär Vinter is the only company in the world that enables waterproofing work to be carried out during the winter months at no additional cost.

Like its sister product, SPS Primary Winter offers effective sealing of circuit boards on almost all surfaces and allows work to continue after at least 24 hours of curing time. SPS Primary Winter has been tested for compatibility with acrylic paints, sealants and tile adhesives of different qualities. The product can be used by all professionals and does not require certification or an epoxy resin course. However, TWO Teknik ApS is happy to assist you with training, ongoing monitoring and support with quality assurance.

SPS Primary has been tested for diffusion by Danish Environmental Analysis and tests show barrier properties of more than 95%.







## FACT:

- Hardens at just 1 degree
- Effectively reduces outgassing by more than 95%
- **Recommended by several of the** • country's leading consulting engineers •
- Can be used as an emergency solution, • as SPS stops the degassing with stone • Allows further work after 24 with immediate effect
- Saves costly demolition and reconstruction of secondary building parts containing PCBs
- Free of solvents and emits no harmful • emissions

- Leaves a clear and smooth surface that can be reworked
- Can be tinted in several colors, also Deltanes for increased KS
- Saves costly additional winter months measures
- hours
- Can be combined with the seal tracer seal
- Is continuously tested and controlled



SPS PRIMÆR is a patent application. The SPS series is specifically designed for PCB problems and is developed and produced in Denmark.



Easy to apply with brush, roller and spray!



For yderligere info: Se sikkerhedsdatablad, Produktblad og evt. kontakt TWO Teknik ApS www.twoteknik.dk Tlf: 72302031