

SPS PRIMÆR - PCB LOCK

TWO SPS is a high-tech diffusion barrier, specially designed to stop the outgassing from PCB-containing surfaces. TWO SPS has been thoroughly tested and the effect is well documented, tests show that TWO SPS can reduce the outgassing from a PCB-containing surface by more than 90%, over a period of more than 10 years*. Sealing with TWO SPS offers two options for sealing PCBs: A) Sealing PCB-containing joints

– The primary sources of PCBs. The PCB-containing joints and surfaces can be sealed, as a temporary solution, to stop the outgassing here and now. This gives time and opportunity for a thorough planning of the actual PCB remediation, in an economic and rational way, for example to wait with the remediation of a window joint until the window needs to be replaced for reasons of energy or age.

B) Sealing of PCB-containing joint flanks

– The secondary sources of PCBs. After remediation of the PCB joint itself, the surrounding PCB-containing materials are sealed, instead of tearing them down. This solution saves the very expensive demolition, disposal and re-establishment, and not least the time involved, and at the same time protects the SPS seal against a new polluted indoor climate from the surrounding (secondary degassing) PCB-containing materials.

** Test in laboratory performed as accelerated test, and shows a time period of min. 10 years and max. 25 years. (The effect thereafter has not been tested).*

FACT:

- Effectively reduces outgassing by more than 90%
- Recommended by several of the country's leading consulting engineers
- Can be used as an emergency solution, since SPS stops the degassing with stone immediate effect
- Saves costly demolition and re-establishment of secondary PCB containing building parts
- Free of solvents and emitters no harmful intrinsic emissions
- Leaves a clear and smooth surface, that can be post-processed
- Contains several types of UV fluorine stage that contributes to an expanded KS programme
- Is under ongoing control and testing



SPS PRIMÆR is a patent application. The SPS Series is specifically developed for PCB problems, is Danish developed and produced.

 TWO Teknik
Contact us for more information:
Tel. 7230 2031

Easy to apply
with brush, roller or
syringe!