

# SPS SEAL TRACE®

## PRODUCT DESCRIPTION:

SPS SEAL TRACE® is a specialized substance designed for testing the integrity of a sealed PCB-containing surface.



## APPLICATION:

Suitable for indoor and outdoor use on various surfaces.




SPS SEAL TRACE® is transparent and does not leave any visible marks. Nevertheless, it can desiccate oily surfaces.



A representative portion of the PCB-containing surface designated for sealing is chosen for the application of SPS SEAL TRACE®. It is advised by SPS SEAL TRACE® to apply it consistently using a standardized approach, especially when dealing with various rooms/areas, to facilitate future documentation and monitoring.



Prior to application, ensure the surface is dry and clear of dust. Apply SPS SEAL TRACE® meticulously using a brush to visibly moisten the surface. A single coat of SPS SEAL TRACE® suffices, drying rapidly. Additional sealing can be done right after applying the tracer.



## IMPORTANT WHEN APPLYING:

If SPS SEAL TRACE® is applied to areas that are later sealed, spilled, or dripped on, the tracer's effectiveness diminishes. This is because it will be naturally dispersed in the air, affecting any future measurements.



## MEASUREMENT VERIFICATION:

When conducting follow-up assessments for SPS SEAL TRACE®, air sampling is performed similarly to PCB measurements, allowing for the measurement of both PCBs and SPS SEAL TRACE® in a single sample. HØJVANG LABORATORIER A/S possesses expertise in analyzing SPS SEAL TRACE® and is available to provide guidance on the analysis process.



## SPECIFICATIONS:

Includes: Trace substance and ethanol.  
Application: 1 round.  
Color: Colorless.  
Drying Time: None.  
Range: Tailored to the surface.  
Thinning: Non-dilutable.  
Cleaning: Tools are tightly wrapped post-use and can be reused.  
Waste: Sorted and disposed of conventionally as painting tools.  
Storage: Keep away from children.

Safety Guidelines for Painting Work  
(FLAMMABLE)

## ADVANTAGE:

- Facilitates management of the sealing effect, anytime
- Specially designed for PCB sealing
- Simple to apply with no drying time
- Suitable for use on all surfaces

 TWO Teknik phone number: 72 30 20 31