

SPS PRIMÆR

Product description

SPS PRIMÆR is a premium two-component diffusion barrier made from top-quality silicates, suitable for all surfaces. Free from solvents and biphenyls.



APPLICATION:

Suitable for indoor and outdoor use on all surfaces containing PCBs, including walls, ceilings, and more. SPS PRIMARY adheres well to various surfaces, especially mineral surfaces like concrete, brick, and plaster. Prior to utilization, the surface should be dry, devoid of loose debris and dust. Exceptionally smooth surfaces may benefit from a gentle sanding to enhance adhesion.

SPS PRIMARY is distinctive in that it can be sprayed on or applied effortlessly with a roller or brush. Always remember to utilize goggles and gloves for work, along with respiratory protection when using a sprayer!

SPS PRIMARY should be applied in a minimum of 2 coats with approximately 30 minutes between each coat (or when the tape is dry) upon completion of the process.

During the solder paste stencil printing process, it is crucial for the solder paste to form a dense and uniform film on the surface. Any dry areas should be re-treated until fully saturated.

AFTER PROCESSING:

Following a 24-hour curing period, work can resume on the surface. Prior to repainting, a test should be conducted, in a more discreet location to assess compatibility. Priming the surface before painting or filing may be required in certain instances.

SPS PRIMARY is compatible with a variety of joint types, paints, and tile adhesives (testing is recommended to verify adhesion). SPS PRIMARY is transparent.

SPECIFICATIONS:



Contains:	High-quality silicate blend and accelerator.
Application:	Minimum of 2 laps.
Color:	Colorless
Curing duration:	24-hour period at 12 degrees.
Application:	Brush, roller, or sprayer.
Range:	4-8 square meters per liter, depending on the surface's nature.
Dilution:	Non-dilutable.
Cleaning:	Tools are not reusable once they have been used.
Waste:	Arranged and stored as paint.
Storage:	Keep away from children's reach.

Safety regulations for painting work 93: 00-03 (Respiratory protection is unnecessary, when applying with a roller and brush, cause SPS PRIMARY does not include solvents).

When working on larger surfaces, ensure proper ventilation to minimize exposure to solvents.

ADVANTAGE:

- Easy to apply and has a short curing time.
- Contains no solvents and does not require an EPOXY course-
- Recommended by the country's leading advisors.
- Is Danish produced.
- Is under continuous testing and control.