

PRODUCT SHEET

SPS - FIBERFORSEGLER

SPS Fiber Sealer is a sealing product specially designed to permanently* and effectively attach unwanted asbestos fibers to a surface and thus prevent the items from becoming airborne. SPS FIBER is designed to be part of a professional renovation of building parts/surfaces with the greatest possible consideration for the user and the environment.

SPS FIBER must never precede a thorough asbestos removal but must be used as an addition to asbestos removal.

Areas of application

For permanent* bonding of fibres from e.g. asbestos to all mineral surfaces, wood and metal.

Application

Apply with a pressure sprayer, brush or roller until a uniform and fully covering layer.

Curing time

1-3 hours depending on temperature and humidity.

Coverage

8-10m² per liter



FREE OF SOLVENTS



WATER-BASED



DIFFUSION-OPEN



FOR INDOOR AND OUTDOOR USE

* Lifespan/adhesion minimum 5 years, excluding influence from UV, moisture and temperatures.

TECHNICAL DATA:

- **Product: 1-component Water-based**
- **MAL Code: 0-1**
- **Density: 1020 kg/m³**
- **Potlife: Approx. 120 days with lid**
- **Touch dry: 1-3 hours**
- **Cured for further work: 24 hours**
- **VOC content: <20g/L**

The SPS series is specifically developed for indoor climate issues, is Danish developed and produced. All our products are manufactured with the greatest possible consideration for the user and the environment.

FEATURES

- Staples are effective fibers such as asbestos on all surfaces
- Water-based
- Diffusion-open
- Fire tested
- Permanent* product
- Free from solvents, epoxy, phthalates and other substances harmful to health
- Hardens in 1-3 hours
- Traceable with UV Fluorescence
- Apply with spray/brush
- Light pink fave at layout
- Transparent after curing
- Can be overdone



Contributes to less hazardous chemicals in the working environment

Under continuous testing and documentation of:



 TWO Teknik

**Permanent
sealing of
Asbestos**